



Retail



Hospitality



Ticketing



Kiosk



Dual



Affordable & Reliable!

3 inch POS printer


- 2" or 3" paper choice
- Stand-alone or wall-mount
- Dual communication interface
- Reliable printing performance



HIGHLIGHTS

2" or 3" paper choice

This two-in-one printer is equipped with a 2" partition, in which you can instantly change whether you desire 2 or 3 inch receipt. No need for utility or dip switch changes.



Stand-alone or wall-mount

We have designed the printer to mount directly to the wall effortlessly without any additional accessories. Use this hole to secure the printer directly to your wall for space-saving convenience. Internal fixture keeps paper in place during printing for smooth printing job every time.




Dual communication interface

- USB V2.0 FS + Ethernet
- USB V2.0 FS + Serial
- USB V2.0 FS + Parallel



Reliable Printing Performance

- Fast printing speed: up to 200 mm/sec
- High reliability mechanism : 1.5 million cuts auto cutter, 150 km TPH
- Outstanding printing of fonts, graphics, and barcode symbologies



SPECIFICATIONS

Print Characteristics

Print Method : Direct Thermal
Print Speed : 200 mm/sec
Print Resolution : 180 dpi
Sensor : Paper End, Cover Open

Media Characteristics

Media Type : Receipt
Media Width : 80 mm
Media Roll Diameter : Up to 80 mm
Supply Method : Easy Paper Loading

Physical Characteristics

Dimensions (WxLxH) : 153 x 195 x 145 mm (6.02 x 7.68 x 5.70 inch)
Weight : 1.44 kg (3.17 lbs.)
Power : EnergyStar Certified,
External Power Adaptor 100-240V AV, 50/60Hz

Drawer Port : 2 ports

Performance Characteristics

Memory : 64 Mbit SDRAM, 16 Mbit FlashROM
NV Image Memory : 256 Kbytes (mono)
Receive Buffer : 4 Kbytes
User Define Buffer : 12 Kbytes
Interface : Dual Interface
Serial + USB 2.0 FS
Parallel + USB 2.0 FS
Ethernet + USB 2.0 FS

Environment Characteristics

Temperature : Operating: 0~45°C (32~113°F)
Storage: -20~60°C (-4~140°F)
Humidity : Operating: 10 ~ 80% RH
Storage: 10 ~ 90% RH

Reliability

Printer Unit : 60 million lines
TPH : 150 km
Auto Cutter : 1.5 million cuts

Software

Emulation : BXL / POS
Driver : Windows Driver, OPOS Driver, JPOS Driver, Linux CUPS Driver,
Mac Driver, Virtual COM USB/Ethernet Driver, Utility Program
SDK : Android SDK

Fonts / Graphics / Symbologies

Character Size : Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24
KOR, CHN, JPN: 24x24
Characters Per Line : Font A: 42 Font B, C: 56 / KOR, CHN, JPN: 21
Character Sets : Alphanumeric: 95
Extended Graphics: 128 x 37 page
International: 32

Graphics : Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbologies : 1D: Coda Bar, Code39, Code93, Code128,
EAN-8, EAN-13, ITF, UPC-A, UPC-E
2D: PDF417, QR Code